

EZI-LOADA

A light weight ramp with enhanced safety that delivers on quality, performance and is cost effective. European designed and engineered, the new Digga Ezi Loada ramps are the most advanced design on the Australian market today.



Features:

- 3 ways of attaching the ramps
 - > Pin (supplied)
 - > Tongue (supplied)
 - > Chain (chain not supplied)
- Patented, fully extruded, double T-beam design, interlocks the rungs into the body of the rail. No physical load is taken by the weld alone. The welds (top & bottom), hold the rung in its fitted position, adding superior strength & durability.
- Certified to the highest international standards CE guaranteeing the quality and safety of the ramps.
 - ISO 9001:2015 - European CE standard
- Reinforced, easy load, lead on/off design are safer and more durable than conventional ramp designs.
- The reinforced bottom rung sits low to the ground ensuring machines don't have to 'step up' onto the ramp. As a result the bottom few rungs won't bend, as so often is the case with current ramp designs. The ride is also much smoother.

RUBBER TRACKS AND WHEELS							
Capacity @ Wheelbase	Code	Beam	Int Width	Ext Width	Weight	Length	Max Deck Height
1.5t @ 1m	LR152530	64mm	255mm	300mm	14kg	2500mm	987mm
2.0t @ 1m	LR233030	100mm	300mm	360mm	23kg	3000mm	1076mm
3.0t @ 1.5m	LR303030	115mm	300mm	360mm	26kg	3000mm	1076mm
3.0t @ 1.5m	LR303535	120mm	350mm	410mm	36kg	3500mm	1258mm
3.5t @ 1.5m	LR353535	125mm	350mm	410mm	37kg	3500mm	1258mm
4.0t @ 1.5m	LR403545	140mm	450mm	510mm	46kg	3500mm	1258mm
4.7t @ 1.5m	LR473545	155mm	450mm	510mm	46kg	3500mm	1258mm
4.7t @ 1.5m	LR473550	155mm	500mm	560mm	51kg	3500mm	1258mm
5.9t @ 1.5m	LR593545	150mm	450mm	510mm	53kg	3500mm	1258mm

STEEL TRACKS AND RUBBER TRACKS / WHEELS							
Capacity @ Wheelbase	Code	Beam	Int Width	Ext Width	Weight	Length	Max Deck Height
6.2t @ 2.0m	LRU593550	150mm	500mm	560mm	60kg	3500mm	1258mm
7.0t @ 2.0m	LRU663550	170mm	500mm	560mm	61kg	3500mm	1258mm
9.0t @ 2.0m	LRU823550	180mm	500mm	560mm	77kg	3500mm	1258mm