



The Slasher is a slashing attachment for skid steer loaders which can be used for the effective cutting and clearing of grass and low ground shrubbery.

Features:

- Available with fixed or side shift frame
- Twin blade dual rotation single cutting bar
- 3 widths available; 1250mm (49"), 1500mm (59"), 1800mm (70")
- Chain curtain for debris suppression - New legislation
- Heavy duty construction - built for Australian conditions
- Also available for mini loaders and excavators
- Rounded side skids for smoother manoeuvrability over uneven terrain

Accessories:

Comes complete with hoses, couplers and fixed mount multifit frame to suit parent machine. Side shift frame optional extra.

Ideal Use:

Landscaping, agriculture, roadway maintenance, general slashing, park maintenance.

Machine Suitability:

Available to suit all skid steer loaders. Excavator models available.

Specifications	1250mm	1500mm	1800mm	1800mm HF
Machine Suitability	Small Skid Steers	Standard Skid Steers	Standard Skid Steers	High Flow Skid Steers
Weight	295 Kg	370 Kg	470 Kg	499 Kg
Length	1700 mm	1860 mm	2115 mm	2115 mm
Width	1443 mm	1630 mm	1930 mm	1930 mm
Height	600 mm	605 mm	665 mm	705 mm
Max Pressure	240 bar	240 bar	240 bar	240 bar
Cutting Height	45mm & 85mm	70mm & 110mm	70mm & 110mm	70mm & 110mm

